



■ SPECIFICATIONS

- Voltage Rating : 125V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000M Ω min.
- Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m Ω max.

■ HOUSING

- Poles : 1 - 6
- Material : Contact : Brass, Tin plated
Base : Nylon 66 UL94V-0
- Q' ty : 1,000 pcs./Bag

Poles	Dimensions(mm)	
	A	B
1	-----	6.00
2	See the Drawing	
3	10.0+(8.0x1)	24.00
4	10.0+(8.0x2)	32.00
5	10.0+(8.0x3)	40.00
6	10.0+(8.0x4)	48.00

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Karen		TOLERANCE 容許公差 .0 ±0.3 .00 ±0.2 .000 ±0.1	PART NAME 品名 JST 10-8.0mm HOUSING 1XXXP BLACK ROHS LOW-LEAD
DWG. 製圖 Yumi	SCALE 比例 參考	UNIT 單位 M M	PART NO. 料號 H1080-XXPB0000R
DATE 制表日 2011/06/01	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4	