


P.B.C LAYOUT  
TOP VIEW ±0.05

MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)  
SHELL: STAINLESS STEEL, TIN PLATING  
TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX  
DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE  
CONTACT RESISTANCE: 30m OHMS MAX  
INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V  
OPERATION TEMPERATURE: -25°C~+105°C

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	 TOLERANCE X ±0.30 XX ±0.25 XXX ±0.150 Ang. ±2°	PART NAME 品名 MICRO USB 3.0 VERSION B TYPE 10P FEMALE SMT TYPE SHIELD FOOT:DIP TYPE BLACK COLOR REEL PACKING ROHS
DWG. 製圖	BETTY		SCALE 比例 參考
DATE 制表日	2010/09/30	UNIT 單位	M M
		PAGE 張數	1 OF 1
		SIZE 紙張尺寸	A 4
		REV. 版次	A
		PART NO. 料號	C8348-10BFBXBRR